

## Loading Your Rented Canoe(s)

Transporting a canoe(s) is very simple and economical. Our staff is there to assist you, give tie-down instructions and help you lift the canoe(s) if you require. **(Please note that it is the customer's responsibility to tighten the canoe(s) to their vehicle ensuring the canoe(s) are stable and secure before they leave our location.)**

### One Canoe one Vehicle

**Cost: \$4**

**Includes: 4 canoe foam pads & adjustable tie-down straps that won't scratch your car.**

#### Step 1

- Place the canoe on the ground beside your vehicle. Make sure it is positioned equally from front to back parallel to your car.

#### Step 2

- Attach the 4 foam pad to the gunnels of the canoe so that once the canoe is lifted onto your vehicle the pads will rest on the roof the car.

#### Step 3

- Lift the canoe onto the roof your car. Please ask our staff for assistance if you need it. Please ensure the yoke of the canoe is not resting on the roof of your car.

#### Step 4

- Attach the tie-down straps to the ends of the canoe.

#### Step 5

- Secure the tie-down straps to a strong metal brace or hook under both the front and rear bumpers of your car.

Every vehicle is different and it may be difficult to find a good place to secure the straps. If you are having trouble please let our staff know.

We can provide you with Quick Loops which are a very handy attachment that fit securely under your car's hood or trunk. They won't scratch your car and give you instant stable and strong hooks.

#### Step 6

- Tighten every strap and secure them with a knot. Give the canoe a test shake and you are ready to go!

## Two Canoes one Vehicle

**Cost: \$8**

**Includes: 2 padded roof top racks, adjustable tie down straps that won't scratch your car & rope.**

### Step 1

- Place the canoes on the ground with one on each side of your vehicle. Make sure they are positioned equally from front to back parallel to your car.

### Step 2

- Place the padded roof top racks on the roof of your car. Adjust the width so that they are centered on your car.

### Step 3

- Lift one canoe at a time onto the roof racks. Ask a friend to lightly brace one canoe by holding it at its side while the other canoe is being lifted onto the car.

### Step 4

- Attach the tie-down straps to the ends of the canoes.

### Step 5

- Secure the tie-down straps to a strong metal brace or hook under both the front and rear bumpers of your car.

Every vehicle is different and it may be difficult to find a good place to secure the straps. If you are having trouble please let our staff know.

We can provide you with Quick Loops which are a very handy attachment that fit securely under your car's hood or trunk. They won't scratch your car and give you instant stable and strong hooks.

### Step 6

- Tighten the straps slowly just so everything is stable.

### Step 7

- Attach a rope to end of one roof rack and toss it diagonally over both canoes. Tighten the rope and secure it around the other end of the roof racks.

### Step 8

- Re-Tighten the tie-down straps so that the canoes are secure. Tie off the straps with a knot.

Give the canoes a test for stability and you are ready to go!